


Design: O/M + Bartenbach GmbH  
Ceiling-recessed luminaire with aluminium die-cast body with electrostatic 100% polyester paint finish. Focal-lens with complex surfaces to provide a focal point through an 8mm aperture for low glare illumination.  
Supplied with fermacell® plasterboard fiber recessing accessory or plasterboard.  
Driver to be ordered separately.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam  
IP65




 2700K	Light Source	Luminaire
Power	5,6W	5,6W
Flux	460lm	240lm
Efficiency	82lm/W	43lm/W
LOR	-	52%
UGR	-	<19



Beam angle  
Medium 35°

Application



Weight  
0,96Kg



● .02 Black / RAL 9005

**Mandatory**

**59009 Driver On/Off [1 to 3 luminaire]**

146,5x43,5x30mm

**59010 Driver On/Off [3 to 6 luminaires]**

115,5x76x30mm

**59011 Driver DALI [1 luminaire]**

95x53x30mm

**59012 Driver DALI [up to 4 luminaires]**

124x78x22mm

## Optional

**59013** Ceiling access hatch for drivers

365x365x13mm

**59034** Plasterboard metal profile for Nub

250x47x18mm

Optional (positioned at the factory)

**59001 1/4 CTO**

ø17x1mm

59002 1/2 CTO

ø17x1mm

59003 Louvre

ø17x3mm

**59004 Soft diffuser**

ø17x1mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains a light source of efficiency class G

Model Identifier 4053560138