

19W / 1630lm / 2700K / On/Off / Flood 46° /
ø100mm

60359



Design: O/M

Ceiling-recessed luminaire made of aluminium die-cast.

Recessing accessory for flush version supplied separately.


LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



LED	2700K	Light Source	Luminaire
Power	19W		23,2W
Flux	2060lm		1630lm
Efficiency	108lm/W		70lm/W
LOR	-		79%
UGR	-		<22



Beam angle Flood 46°
Application
Weight 0,5Kg



Finishes

- .04 Matt White
- .05 Matt Black

Optional

- 59066 Flush accessory (12.5mm ceilings)
201x17mm
- 59067 Flush accessory (15mm ceilings)
201x19,5mm
- 59068 Flush accessory (25mm ceilings)
201x29,5mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier BXR-27G2000-C-73