




Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing accessory for flush version supplied separately.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz




 2700K	Light Source	Luminaire
Power	10W	12,5W
Flux	1100lm	870lm
Efficiency	110lm/W	70lm/W
LOR	-	79%
UGR	-	<22



Beam angle
Flood 46°

Application



Weight
0,5Kg



Ø95 (trim version)



- Finishes
- .04 Matt White
 - .05 Matt Black

- Optional
- 59066** Flush accessory (12.5mm ceilings)
201x17mm
 - 59067** Flush accessory (15mm ceilings)
201x19,5mm
 - 59068** Flush accessory (25mm ceilings)
201x29,5mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com
The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 |2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier BXR-27G2000-C-73