



Design: O/M

Ceiling-recessed luminaire made of aluminium die-cast.

Recessing accessory for flush version supplied separately.

LED CRI>80 / >50.000h, L80/B10
3-step MacAdam / power supply included
IP54 | 230Vac | 50/60Hz




| LED | 3000K | Light Source | Luminaire |
|------------|---------|--------------|-----------|
| Power | 19W | | 23,2W |
| Flux | 2180lm | | 1240lm |
| Efficiency | 115lm/W | | 54lm/W |
| LOR | - | | 57% |
| UGR | - | | <28 |



| | |
|-------------|-------|
| Beam angle | 105° |
| Diffuse | |
| Application | |
| Weight | 0,5Kg |



Ø95 (trim version)



Finishes

- .04 Matt White
- .05 Matt Black

Optional

- 59066** Flush accessory (12.5mm ceilings)
201x17mm
- 59067** Flush accessory (15mm ceilings)
201x19,5mm
- 59068** Flush accessory (25mm ceilings)
201x29,5mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com
The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 |2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class E
Model Identifier BXR-30E2000-C-90