



Design: O/M

Ceiling-recessed luminaire, with aluminium body with 25micron maximum corrosion resistance anodization. Trim aluminium with matt finish or with textured electrostatic 100% polyester paint.

Tempered clear glass.

Supplied with cable (2x0,50mm²).


Driver to be ordered separately.

Values for 700mA. For 350mA estimate half of the indicated values.

LED CRI>90 / >50.000h, L80/B10 / 3-step MacAdam

IP67 | 350mA / 700mA



 LED	2700K	Light Source	Luminaire
Power	2,2W		2,2W
Flux	200lm		95lm
Efficiency	91lm/W		43lm/W
LOR	-		48%
UGR	-		<28



Beam angle

Diffuse

Application



Weight

0,07Kg



## Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .12 Brushed stainless steel
- .34 Rust

## Mandatory

- 59124** 15W Driver  
1 to 10 luminaires / 350mA
- 59125** 8W Driver  
1 to 5 luminaires / 350mA
- 59126** 15W Driver  
1 to 10 luminaires / 350mA
- 59127** 25W Driver  
5 to 18 luminaires / 350mA
- 59128** 11W Driver  
1 to 4 luminaires / 700mA
- 59129** 35W Driver  
1 to 12 luminaires / 700mA
- 59130** 17W Driver  
1 to 5 luminaires / 700mA
- 59131** 48W Driver  
1 to 18 luminaires / 700mA

## Optional

- 27400** IP68 Connector 2 way  
4 poles
- 27395** IP68 Pass-through wiring connection box  
3 way