

43W / 4800lm / 4000K / DALI / Wide flood
76° / 2353mm

60526

Product timing available by request



Design: OM + Bartenbach GmbH
Surface or pendant luminaire with housing made of aluminium with 25 micron maximum corrosion resistance anodization in matte finish or electrostatic 100% polyester paint with textured finish. Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured finish.

Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.

Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



| LED | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 43W | 49,9W |
| Flux | | 6000lm | 4800lm |
| Efficiency | | 142lm/W | 96lm/W |
| LOR | | - | 80% |
| UGR | | - | <19 |



Beam angle
Wide flood 76°

Application



Weight
3,8Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

54036 Pendant direct fitting accessory

56051 Clear Base DALI

ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com