

26W / 2480lm / 4000K / DALI / Medium 31° /
 611mm

60691


Design: O/M + Bartenbach GmbH

Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision35 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source.

Fitting accessories for pendant version ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		26W	31,7W
Flux		3400lm	2480lm
Efficiency		131lm/W	78lm/W
LOR		-	73%
UGR		-	<10


 Beam angle
Medium 31°

Application


 Weight
1,2Kg

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory
54036 Pendant direct fitting accessory

56051 Clear Base DALI

ø60x35mm

 For the specific supply of "DALI 2" drivers, please contact:
 support@om-light.com