


7,9W / 730lm / 3000K / On/Off / Diffuse /  
559mm

60878

Design: O/M  
LED light source with good colour consistency and  
long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz




- |                       |                       |
|-----------------------|-----------------------|
| <b>Structure</b>      | <b>Diffuser</b>       |
| 1 Profile             | A Polycarbonate frost |
| 2 End caps            | diffuser              |
| 3 Fitting accessories | <b>Light Source</b>   |
| 4 Profile coupling    | B LED Modules         |

LED	3000K	Light Source	Luminaire
Power		7,9W	9,9W
Flux		1430lm	730lm
Efficiency		181lm/W	74lm/W
LOR		-	51%
UGR		-	<25



Beam angle  
Diffuse



Weight  
0,5Kg



**Finishes**  
Choose the length and layout of the system exactly as you want it, to  
model the right lighting functions for different tasks. For further  
information please contact: support@om-light.com

Data according to regulations  
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class C  
Model Identifier 89603216

