

24W / 1950lm / 2700K / On/Off / Diffuse /  
1679mm

61314

Design: O/M

LED light source with good colour consistency and  
long operation lifespan.LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz**Structure**

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

**Diffuser**A Polycarbonate frost  
diffuser**Light Source**

B LED Modules

| LED        | 2700K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power      |       | 24W          | 29,3W     |
| Flux       |       | 4200lm       | 1950lm    |
| Efficiency |       | 175lm/W      | 67lm/W    |
| LOR        |       | -            | 46%       |
| UGR        |       | -            | <25       |

Beam angle  
Diffuse

Application

Weight  
0,6Kg**Finishes**Choose the length and layout of the system exactly as you want it, to  
model the right lighting functions for different tasks. For further  
information please contact: [support@om-light.com](mailto:support@om-light.com)**Data according to regulations**2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class D  
Model Identifier 89603215