

27W / 2440lm / 4000K / DALI / Diffuse /
1119mm

61391

Design: O/M
LED light source with good colour consistency and
long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz




- | | |
|-----------------------|-----------------------|
| Structure | Diffuser |
| 1 Profile | A Polycarbonate frost |
| 2 End caps | diffuser |
| 3 Fitting accessories | Light Source |
| 4 Profile coupling | B LED Modules |

| LED | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 27W | 32,9W |
| Flux | | 5200lm | 2440lm |
| Efficiency | | 193lm/W | 74lm/W |
| LOR | | - | 47% |
| UGR | | - | <25 |



Beam angle
Diffuse

Application



Weight
0,57Kg



Finishes

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com
Choose the length and layout of the system exactly as you want it, to
model the right lighting functions for different tasks. For further
information please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class C
Model Identifier 89603217