

20W / 1775lm / 4000K / DALI / Diffuse /
1399mm

61392

Design: O/M

LED light source with good colour consistency and
long operation lifespan.LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz

Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

Diffuser

A Polycarbonate frost
diffuser

Light Source

B LED Modules

| LED | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 20W | 24,4W |
| Flux | | 3775lm | 1775lm |
| Efficiency | | 189lm/W | 73lm/W |
| LOR | | - | 47% |
| UGR | | - | <25 |

Beam angle
Diffuse

Application

Weight
0,58Kg

Finishes

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.comChoose the length and layout of the system exactly as you want it, to
model the right lighting functions for different tasks. For further
information please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class C
Model Identifier 89603212, 89603217