

## U120 Surface/Pendant

95W / 7000lm / 3000K / On/Off / Diffuse /  
2891mm

62030



Design: Eduardo Souto de Moura

Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.

Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP40 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power		95W	109W
Flux		11300lm	7000lm
Efficiency		119lm/W	64lm/W
LOR		-	62%
UGR		-	<25



Beam angle  
Diffuse

Application



Weight  
12,9Kg



### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

### Mandatory

54036 Pendant direct fitting accessory

54034 Clear Base

ø60x35mm

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class D

Model Identifier WU-M-526-S-BC-830, WU-M-536-S-BC-830