


U120
Surface/Pendant

174W / 14500lm / 3000K / On/Off / Diffuse /
2891mm

62031



Design: Eduardo Souto de Moura
Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint. Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.
Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP40 | 230Vac | 50/60Hz



LED 3000K	Light Source	Luminaire
Power	174W	201W
Flux	23500lm	14500lm
Efficiency	134lm/W	72lm/W
LOR	-	62%
UGR	-	<25



Beam angle
Diffuse

Application



Weight
12,9Kg



- Finishes
- .01 White / RAL 9010
 - .02 Black / RAL 9005
 - .10 Anodised aluminium

Mandatory
54036 Pendant direct fitting acesory
54034 Clear Base
ø60x35mm

Data according to regulations
2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class D
Model Identifier WU-M-526-S-BC-830, WU-M-536-S-BC-830