

U120

Made-to-measure

48W / 4150lm / 4000K / On/Off / Diffuse /
1429mm

62150

Design: O/M

LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

Diffuser

- A Polycarbonate frost diffuser

Light Source

- B LED Modules

| LED 4000K | Light Source | Luminaire |
|------------|--------------|-----------|
| Power | 48W | 56,5W |
| Flux | 6700lm | 4150lm |
| Efficiency | 140lm/W | 73lm/W |
| LOR | - | 62% |
| UGR | - | <25 |



Beam angle
Diffuse

Application



Weight
0,51Kg



Finishes

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C
Model Identifier WU-M-526-S-BC-840, WU-M-536-S-BC-840

