

27+20W / 2440+1480lm / 4000K / DALI /  
Diffuse / batwing / 1119mm

62325

Design: O/M

LED light source with good colour consistency and  
long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



### Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

### Diffuser

A Polycarbonate frost  
diffuser

### Light Source

B LED Modules

LED	4000K	Light Source	Luminaire
Power		27+20W	32,9+24,4W
Flux		5200+2360lm	2440+1480lm
Efficiency		161lm/W	68lm/W
LOR		-	52%
UGR		-	<25



Beam angle  
Diffuse / batwing

Application



Weight  
0,58Kg



### Finishes

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

Choose the length and layout of the system exactly as you want it, to  
model the right lighting functions for different tasks. For further  
information please contact: support@om-light.com

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class C  
and E

Model Identifier WU-M-594-840, 89603217