

32W / 4520lm / 4000K / DALI / Diffuse /  
2312mm

62556



Design: Eduardo Souto de Moura

Surface or pendant luminaire with tubular shock-resistant frosted polycarbonate body with 50mm diameter.

Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that prevents condensation within luminaire. Fitting accessories ordered separately.


LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP67 | IK08 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		32W	37,6W
Flux		6040lm	4520lm
Efficiency		189lm/W	120lm/W
LOR		-	75%
UGR		-	<25




Beam angle  
Diffuse

Application



Weight  
2,3Kg



Finishes

● .25 Frost

Mandatory

43702 Surface fitting accessory (>2000mm)

43706 Pendant fitting accessory (>2000mm)

Optional

59061 Stainless steel fitting accessory (>2000mm)

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class B  
Model Identifier 28004774