

## Tubo 50

14W / 1790lm / 2700K / DALI / Diffuse /  
632mm

62567



Design: Eduardo Souto de Moura

Surface or pendant luminaire with tubular shock-resistant frosted polycarbonate body with 50mm diameter.

Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that

prevents condensation within luminaire.


Fitting accessories ordered separately.


LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP67 | IK08 | 230Vac | 50/60Hz



 LED	2700K	Light Source	Luminaire
Power	14W		17,1W
Flux	2390lm		1790lm
Efficiency	171lm/W		105lm/W
LOR	-		75%
UGR	-		<28




Beam angle  
**Diffuse**

## Application



Weight  
1Kg



## Finishes

☐ .25 Frost

## Mandatory

**43701** Surface fitting accessory

**43705 Pendant fitting accessory**

## Optional

**59057** Stainless steel fitting accessory

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

## Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class C  
Model Identifier 28004771