

## O975 Surface/Pendant

51W / 4100lm / 3000K / DALI / Diffuse /  
1160mm

62709

Design: Eduardo Souto de Moura

Surface or pendant luminaire with housing made of anodised aluminium profile with matt or textured-paint finish and frosted polycarbonate diffuser with user friendly clipping system.

5mm frosted polycarbonate end caps.

Fitting accessories ordered separately.



LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP44 | IK07 | 230Vac | 50/60Hz



| LED        | 3000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power      |       | 51W          | 60W       |
| Flux       |       | 5850lm       | 4100lm    |
| Efficiency |       | 115lm/W      | 68lm/W    |
| LOR        |       | -            | 70%       |
| UGR        |       | -            | <22       |



Beam angle  
Diffuse

Application



Weight  
1,86Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Mandatory

44070 Pendant fitting accessory

Ø60x35mm

44110 Clear base DALI

Ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com