



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.


Includes cable to connect modules with male and female plug connector.

Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.  
IP44 | 48Vdc



 3000K	Light Source	Luminaire
Power	18W	18W
Flux	2080lm	1720lm
Efficiency	116lm/W	96lm/W
LOR	-	83%
UGR	-	-



Beam angle  
Medium 30°

Application



Weight  
0,35Kg



#### Finishes

● .25 Frost

#### Included

Fitting accessories 0°  
34x19x7mm



#### Mandatory

**18105** Power cable  
2x0,35mm<sup>2</sup> (0,5m)  
**18106** Power cable  
2x0,35mm<sup>2</sup> (1m)  
**18820** Power Supply 16W  
On/Off  
**18821** Power Supply 30W  
On/Off  
**18822** Power Supply 55W  
On/Off  
**18823** Power Supply 75W  
On/Off  
**18824** Power Supply 150W  
On/Off  
**18833** LED Dimmer DALI

#### Optional

**18107** Extension cable  
2x0,35mm<sup>2</sup> (1m)  
**18108** Extension cable  
2x0,35mm<sup>2</sup> (5m)  
**18831** Fitting accessories 45°  
45x19,5x20mm