



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.

Includes cable to connect modules with male and female plug connector.


Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.


Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.

IP44 | 48Vdc




|   |              |           |
|---|--------------|-----------|
|  2500K | Light Source | Luminaire |
| Power   | 34W          | 34W       |
| Flux  | 3650lm       | 3050lm    |
| Efficiency  | 107lm/W      | 90lm/W    |
| LOR   | -            | 84%       |
| UGR   | -            | -         |



Beam angle  
Diffuse

Application

Weight  
0,44Kg



#### Finishes

● .25 Frost

#### Included

Fitting accessories O°  
34x19x7mm



#### Mandatory

**18105** Power cable

2x0,35mm² (0,5m)

**18106** Power cable

2x0,35mm² (1m)

**18820** Power Supply 16W

On/Off

**18821** Power Supply 30W

On/Off

**18822** Power Supply 55W

On/Off

**18823** Power Supply 75W

On/Off

**18824** Power Supply 150W

On/Off

**18833** LED Dimmer DALI

#### Optional

**18107** Extension cable

2x0,35mm² (1m)

**18108** Extension cable

2x0,35mm² (5m)

**18831** Fitting accessories 45°

45x19,5x20mm