



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.


Includes cable to connect modules with male and female plug connector.

Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.  
IP44 | 48Vdc




 2200K	Light Source	Luminaire
Power	13,6W	13,6W
Flux	1340lm	1100lm
Efficiency	99lm/W	81lm/W
LOR	-	82%
UGR	-	-



Beam angle  
Medium 30°

Application



Weight  
0,18Kg



#### Finishes

● .25 Frost

#### Included

Fitting accessories O°  
34x19x7mm



#### Mandatory

**18105** Power cable

2x0,35mm² (0,5m)

**18106** Power cable

2x0,35mm² (1m)

**18820** Power Supply 16W

On/Off

**18821** Power Supply 30W

On/Off

**18822** Power Supply 55W

On/Off

**18823** Power Supply 75W

On/Off

**18824** Power Supply 150W

On/Off

**18833** LED Dimmer DALI

#### Optional

**18107** Extension cable

2x0,35mm² (1m)

**18108** Extension cable

2x0,35mm² (5m)

**18831** Fitting accessories 45°

45x19,5x20mm