



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.


Includes cable to connect modules with male and female plug connector.

Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.


Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.  
IP20 | 48Vdc



|  |                     |                  |
|--|---------------------|------------------|
|  <b>3000K</b> | <b>Light Source</b> | <b>Luminaire</b> |
| <b>Power</b>   | <b>6,8W</b>         | <b>6,8W</b>      |
| <b>Flux</b>  | <b>790lm</b>        | <b>440lm</b>     |
| <b>Efficiency</b>  | <b>116lm/W</b>      | <b>65lm/W</b>    |
| <b>LOR</b>   | -                   | <b>56%</b>       |
| <b>UGR</b>   | -                   | -                |



|   |
|---|
| <b>Beam angle</b><br><b>Diffuse</b>   |
| <b>Application</b>  |
|  |
| <b>Weight</b><br><b>0,09Kg</b>  |



#### Finishes

☐ .25 Frost

#### Included

Fitting accessories 0°  
34x19x7mm



#### Mandatory

**18105** Power cable

2x0,35mm<sup>2</sup> (0,5m)

**18106** Power cable

2x0,35mm<sup>2</sup> (1m)

**18820** Power Supply 16W

On/Off

**18821** Power Supply 30W

On/Off

**18822** Power Supply 55W

On/Off

**18823** Power Supply 75W

On/Off

**18824** Power Supply 150W

On/Off

**18833** LED Dimmer DALI

#### Optional

**18107** Extension cable

2x0,35mm<sup>2</sup> (1m)

**18108** Extension cable

2x0,35mm<sup>2</sup> (5m)

**18831** Fitting accessories 45°

45x19,5x20mm