



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.

Includes cable to connect modules with male and female plug connector.

Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.  
IP20 | 48Vdc



LED	3000K	Light Source	Luminaire
Power		6,8W	6,8W
Flux		790lm	440lm
Efficiency		116lm/W	65lm/W
LOR		-	56%
UGR		-	-



Beam angle  
Diffuse

Application



Weight  
0,09Kg



#### Finishes

☐ .25 Frost

#### Included

Fitting accessories 0°  
34x19x7mm



#### Mandatory

**18105** Power cable (500mm)  
2x0,35mm<sup>2</sup> (0,5m)

**18106** Power cable (1000mm)  
2x0,35mm<sup>2</sup> (1m)

**18820** Power Supply 16W  
On/Off

**18821** Power Supply 30W  
On/Off

**18822** Power Supply 55W  
On/Off

**18823** Power Supply 75W  
On/Off

**18824** Power Supply 150W  
On/Off

**18833** LED Dimmer DALI

#### Optional

**18107** Extension cable (1000mm)  
2x0,35mm<sup>2</sup> (1m)

**18108** Extension cable (5000mm)  
2x0,35mm<sup>2</sup> (5m)

**18831** Fitting accessories 45°  
45x19,5x20mm