

27W / 3220lm / 4000K / On/Off / Prismatic /
1119mm

63039

Design: O/M
LED light source with good colour consistency and
long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



- Structure**
 - 1 Profile
 - 2 End caps
 - 3 Fitting accessories
 - 4 Profile coupling
- Diffuser**
 - A Polycarbonate frost diffuser
- Light Source**
 - B LED Modules


| LED | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 27W | 32,9W |
| Flux | | 5200lm | 3220lm |
| Efficiency | | 193lm/W | 98lm/W |
| LOR | | - | 62% |
| UGR | | - | <22 |



Beam angle
Prismatic



Weight
0,57Kg



Finishes

Choose the length and layout of the system exactly as you want it, to
model the right lighting functions for different tasks. For further
information please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class C
Model Identifier 89603217