

## Beam Adjustable

2,2W / 180lm / 2700K / DALI / Spot 14° / ø75mm

63185



Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Adjustable version (orientable by 30° on the horizontal axis and 355° on the vertical axis).  
Recessing accessory for flush version supplied separately.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz



LED	2700K	Light Source	Luminaire
Power		2,2W	2,8W
Flux		200lm	180lm
Efficiency		91lm/W	64lm/W
LOR		-	90%
UGR		-	<10



Beam angle  
Spot 14°

Application



Weight  
0,38Kg



Ø70 (trim version)



### Finishes

- .04 Matt White
- .05 Matt Black

### Optional

- 59063** Flush accessory (12.5mm ceilings)  
176x17mm
- 59064** Flush accessory (15mm ceilings)  
176x19,5mm
- 59065** Flush accessory (25mm ceilings)  
176x29,5mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com  
The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations  
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class F  
Model Identifier 4053560279