



Design: O/M + Bartenbach GmbH  
Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.  
Orientable by 20° horizontal rotation and 355° vertical rotation.  
Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam.  
Recessing accessory supplied separately.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz



LED	2700K	Light Source	Luminaire
Power		5,6W	7W
Flux		460lm	410lm
Efficiency		82lm/W	59lm/W
LOR		-	89%
UGR		-	<19



Beam angle  
Medium 40°

Application



Weight  
0,53Kg



### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

### Mandatory

- 59039 Trimless accessory (12.5mm ceilings)  
155x18mm
- 59040 Trimless accessory (15mm ceilings)  
155x20mm
- 59041 Trimless accessory (25mm ceilings)  
155x30mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class G Model Identifier 4053560312H