

One Adjustable Trimless

5,6W / 200lm / 3000K / DALI / Spot 15° /
ø54mm

63580



Design: O/M + Bartenbach GmbH

Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Orientable by 20° horizontal rotation and 355° vertical rotation.

Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam.

Recessing accessory supplied separately.

LED CRI>90 / >50.000h, L80/B10

2-step MacAdam / Power supply included.

IP20 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power		5,6W	7W
Flux		440lm	200lm
Efficiency		79lm/W	29lm/W
LOR		-	45%
UGR		-	<10




Beam angle
Spot 15°

Application



Weight
0,58Kg



Finishes

○ .01 White / RAL 9010

● .02 Black / RAL 9005

Mandatory

59039 Trimless accessory (12.5mm ceilings)

155x18mm

59040 Trimless accessory (15mm ceilings)

155x20mm

59041 Trimless accessory (25mm ceilings)

155x30mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains a light source of efficiency class G Model Identifier 4053560290H