

## One Adjustable Trimless

5,6W / 215lm / 4000K / On/Off / Spot 15° /  
e54mm

63582



Design: O/M + Bartenbach GmbH

Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Orientable by 20° horizontal rotation and 355° vertical rotation.

Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam.

Recessing accessory supplied separately.


LED CRI>80 / >50.000h, L80/B10

2-step MacAdam / Power supply included.

IP20 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		5,6W	7W
Flux		480lm	215lm
Efficiency		86lm/W	31lm/W
LOR		-	45%
UGR		-	<10




Beam angle  
Spot 15°

Application



Weight  
0,58Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

**59039** Trimless accessory (12.5mm ceilings)

155x18mm

**59040** Trimless accessory (15mm ceilings)

155x20mm

**59041** Trimless accessory (25mm ceilings)

155x30mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class G Model Identifier 4053560313H