

17+35W / 1800+1700lm / 4000K / DALI /
Wide flood 76° / batwing / 1440mm

63783

Product timing available by request



Design: OM + Bartenbach GmbH

Pendant direct and indirect module with housing made of aluminium with electrostatic 100% polyester paint.

Direct light: Linear extruded lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.

Indirect light: Linear lenses for batwing effect protected by a transparent polycarbonate diffuser.


LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



| LED | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-------------|
| Power | | 17+35W | 20,7+41,2W |
| Flux | | 2250+2150lm | 1800+1700lm |
| Efficiency | | 85lm/W | 57lm/W |
| LOR | | - | 80% |
| UGR | | - | <19 |



Beam angle
Wide flood 76° /
batwing

Application



Weight



Finishes

- .04 Matt White
- .05 Matt Black

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com