

21W / 2320lm / 4000K / DALI / Diffuse /
ø400mm

64567

Design: O/M

Recessed luminaire made of aluminium body with electrostatic 100% polyester paint with textured-finish suitable for adverse climate conditions. Frosted acrylic diffuser with perfect light uniformity. Recessing accessories supplied separately.

LED: CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP43 | 230Vac | 50/60Hz





LED	4000K	Light Source	Luminaire
Power		21W	26W
Flux		3430lm	2320lm
Efficiency		163lm/W	89lm/W
LOR		-	68%
UGR		-	<25



Beam angle
Diffuse

Application

Weight
4,5Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

Mandatory

59077 Recessed fitting accessory
Ø398x498x114mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com
Recessed accessory for different ceiling heights under request

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class C
Model Identifier 89603356