




Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP44 | 100mA



 <b>3500K</b>	<b>Light Source</b>	<b>Luminaire</b>
<b>Power</b>	<b>3,7W</b>	<b>3,7W</b>
<b>Flux</b>	<b>410lm</b>	<b>330lm</b>
<b>Efficiency</b>	<b>111lm/W</b>	<b>89lm/W</b>
<b>LOR</b>	-	<b>80%</b>
<b>UGR</b>	-	<b>&lt;13</b>



Beam angle  
**Medium 26°**

Application



Weight  
**0.08Kg**



Finishes

- .04 Matt White
- .05 Matt Black

Mandatory

- 59088** Driver On/Off [100mA]  
138x30x21mm
- 59089** Driver DALI [100mA]  
144x30x21mm
- 59090** Driver PhaseCut [100mA]  
122x41x23mm
- 59091** Driver 1-10V [120mA]  
130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)  
The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class F  
Model Identifier BXRH-35G1000-B-83