




Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP44 | 400mA / 200mA



 2700K	Light Source	Luminaire
	Power	14W / 7W
	Flux	2270lm / 1135lm
	Efficiency	162lm/W
	LOR	80%
	UGR	<13



Beam angle  
Flood 42°

Application



Weight  
0.37Kg



#### Finishes

- .04 Matt White
- .05 Matt Black

#### Mandatory

**59117** Driver On/Off [400mA]

147x43x30mm

**59116** Driver On/Off [200mA]

147x43x30mm

**59119** Driver DALI [400mA]

144x30x21mm

**59118** Driver DALI [200mA]

144x30x21mm

**59121** Driver PhaseCut [400mA]

111x22x52mm

**59120** Driver PhaseCut [180mA]

102x49x29mm

**59123** Driver 1-10V [400mA]

163x30x21mm

**59122** Driver 1-10V [200mA]

130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

The 5-year guarantee applies only when the luminaire and driver are supplied together.

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 [2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E Model Identifier BXRE-27G20FB-C-83