

3,7W / 300lm / 2700K / Flood 42° /
50x50mm


64797



Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply not included
IP44 | 100mA



 2700K	Light Source	Luminaire
Power	3,7W	3,7W
Flux	375lm	300lm
Efficiency	101lm/W	81lm/W
LOR	-	80%
UGR	-	<16



Beam angle
Flood 42°

Application



Weight
0.08Kg



- Mandatory

59088 Driver On/Off [100mA]

138x30x21mm

59089 Driver DALI [100mA]

144x30x21mm

59090 Driver PhaseCut [100mA]

122x41x23mm

59091 Driver 1-10V [120mA]

130x30x20mm

Optional

59148 Louvre

ø25x4mm

59149 Elliptical diffuser

ø25x4mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier BXRH-27G1000-B-83