




Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP65 | 400mA / 200mA



|   |       |                 |                |
|---|-------|-----------------|----------------|
|  LED | 3500K |                 |                |
|   |       | Light Source    | Luminaire      |
| Power   |       | 14W / 7W        | 14W / 7W       |
| Flux  |       | 2320lm / 1160lm | 1755lm / 880lm |
| Efficiency  |       | 165lm/W         | 125lm/W        |
| LOR   |       | -               | 76%            |
| UGR   |       | -               | <19            |



Beam angle  
Flood 60°



Weight  
0.37Kg



#### Finishes

- .04 Matt White
- .05 Matt Black

#### Mandatory

- 59117** Driver On/Off [400mA]  
147x43x30mm
- 59116** Driver On/Off [200mA]  
147x43x30mm
- 59119** Driver DALI [400mA]  
144x30x21mm
- 59118** Driver DALI [200mA]  
144x30x21mm
- 59121** Driver PhaseCut [400mA]  
111x22x52mm
- 59120** Driver PhaseCut [180mA]  
102x49x29mm
- 59123** Driver 1-10V [400mA]  
163x30x21mm
- 59122** Driver 1-10V [200mA]  
130x30x20mm

#### Optional

- 59156** Frosted Glass  
ø52x2mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

The 5-year guarantee applies only when the luminaire and driver are supplied together.

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E  
Model Identifier BXRE-35G20FB-C-83