



Go  
IP65 Square

3,7W / 285lm / 2700K / Flood 60° /  
50x50mm


64862



Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP65 | 100mA



|   |         |              |           |
|---|---------|--------------|-----------|
|  LED | 2700K   | Light Source | Luminaire |
| Power   | 3,7W    | 3,7W         | 3,7W      |
| Flux  | 375lm   | 285lm        | 285lm     |
| Efficiency  | 101lm/W | 77lm/W       | 77lm/W    |
| LOR   | -       | 76%          | 76%       |
| UGR   | -       | <22          | <22       |



Beam angle  
Flood 60°

Application



Weight  
0.08Kg



45x45



#### Finishes

- .04 Matt White
- .05 Matt Black

#### Mandatory

- 59088** Driver On/Off [100mA]  
138x30x21mm
- 59089** Driver DALI [100mA]  
144x30x21mm
- 59090** Driver PhaseCut [100mA]  
122x41x23mm
- 59091** Driver 1-10V [100mA]  
130x30x20mm

#### Optional

- 59140** Flush accessory (12.5mm ceilings)  
110X56X16,5mm
- 59141** Flush accessory (15mm ceilings)  
110X56X19,5mm
- 59150** Frosted Glass  
ø28x2mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F  
Model Identifier BXRH-27G1000-B-83