

Go IP65 Square

**3,7W / 300lm / 3000K / Flood 60° /
50x50mm**

64865




Design: O/M


Ceiling-recessed luminaire made of aluminium die-cast.

Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply not included
IP65 | 100mA



 LED	3000K	Light Source	Luminaire
Power	3,7W		3,7W
Flux	395lm		300lm
Efficiency	107lm/W		81lm/W
LOR	-		76%
UGR	-		<22



Beam angle
Flood 60°


Application



Weight
0.08Kg



45x45



Finishes

- .04 Matt White
● .05 Matt Black

Mandatory

59088 Driver On/Off [100mA]

138x30x21mm

59089 Driver DALI [100mA]

144x30x21mm

59090 Driver PhaseCut [100mA]

122x41x23mm

59091 Driver 1-10V [100mA]

130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier BXRH-30G1000-B-83