




Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP65 | 100mA



 4000K	Light Source	Luminaire
Power	3,7W	3,7W
Flux	415lm	315lm
Efficiency	112lm/W	85lm/W
LOR	-	76%
UGR	-	<16



Beam angle  
Flood 42°

Application



Weight  
0.08Kg



45x45



#### Finishes

- .04 Matt White
- .05 Matt Black

#### Mandatory

- 59088** Driver On/Off [100mA]  
138x30x21mm
- 59089** Driver DALI [100mA]  
144x30x21mm
- 59090** Driver PhaseCut [100mA]  
122x41x23mm
- 59091** Driver 1-10V [100mA]  
130x30x20mm

#### Optional

- 59150** Frosted Glass  
ø28x2mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 [2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F  
Model Identifier BXRH-40G1000-B-83