




Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP65 | 180mA / 100mA



|  |                     |                  |
|--|---------------------|------------------|
|  <b>4000K</b> | <b>Light Source</b> | <b>Luminaire</b> |
| <b>Power</b>   | 6,7W / 3,7W         | 6,7W / 3,7W      |
| <b>Flux</b>  | 720lm / 400lm       | 545lm / 305lm    |
| <b>Efficiency</b>  | 107lm/W             | 81lm/W           |
| <b>LOR</b>   | -                   | 76%              |
| <b>UGR</b>   | -                   | <16              |



**Beam angle**  
**Spot 20°**

**Application**



**Weight**  
**0.21Kg**



65x65



#### Finishes

- .04 Matt White
- .05 Matt Black

#### Mandatory

- 59093** Driver On/Off [180mA]  
147x43x30mm
- 59092** Driver On/Off [100mA]  
92x28x21mm
- 59095** Driver DALI [180mA]  
144x30x21mm
- 59094** Driver DALI [100mA]  
144x30x21mm
- 59097** Driver Phase-Cut [180mA]  
102x49x29mm
- 59096** Driver Phase-Cut [100mA]  
122x41x23mm
- 59099** Driver 1-10V [180mA]  
130x30x20mm
- 59098** Driver 1-10V [120mA]  
130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

The 5-year guarantee applies only when the luminaire and driver are supplied together.

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 [2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F  
Model Identifier BXRH-40G1000-B-83