

5,6W / 430lm / 4000K / On/Off / Flood 56° /  
ø45mm


64892



Design: O/M + Bartenbach GmbH  
Surface spotlight with die-cast aluminium body with  
electrostatic 100% polyester paint finish.  
Orientable by 150° horizontal rotation and 330°  
vertical rotation.  
Driver to be ordered separately.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Driver to be ordered separately.  
IP20 / 450mA



|  |                     |                       |
|--|---------------------|-----------------------|
|  <b>4000K</b> | <b>Light Source</b> | <b>Luminaire</b>      |
| <b>Power</b>   | <b>5,6W</b>         | <b>5,6W</b>           |
| <b>Flux</b>  | <b>460lm</b>        | <b>430lm</b>          |
| <b>Efficiency</b>  | <b>82lm/W</b>       | <b>61lm/W</b>         |
| <b>LOR</b>   | -                   | <b>93%</b>            |
| <b>Operating Condition</b>   | -                   | <b>Current source</b> |



Beam angle  
Flood 56°

Application

Weight  
0,30Kg



#### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

---

#### Mandatory

**59084** Driver On/Off [Up to 2 luminaires]

140x30x21mm

**59085** Driver On/Off [Up to 3 luminaires]

163x30x21mm

**59086** Driver DALI [Up to 2 luminaires]

140x30x21mm

**59087** Driver DALI [Up to 3 luminaires]

163x30x21mm

#### Optional

**59072** 1/4 CTO

ø35x1,1mm

**59073** 1/2 CTO

ø35x1,1mm

**59074** Louvre

ø35x2mm

**59075** Soft diffuser

ø35x2mm

---

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class G  
Model Identifier 4053560313L