

Tubo Pro Surface

53W / 4690lm / 3500K / DALI / Wide flood
76° / 2984mm

64907



Design: Eduardo Souto de Moura
Surface luminaire with tubular semi frosted PMMA body with 70mm diameter.
Clear polycarbonate end caps with marked installation angles.
Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.
Equipped with 2m cable (5x0.75 mm²).
Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
Power supply included.
IP44 | 230Vac | 50/60Hz



| LED | 3500K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 53W | 62,4W |
| Flux | | 6900lm | 4690lm |
| Efficiency | | 130lm/W | 75lm/W |
| LOR | | - | 68% |
| UGR | | - | <16 |



Beam angle
Wide flood 76°

Application



Weight



Finishes

○ .01 White / RAL 9010

Mandatory

59163 Surface fitting accessor (>1600mm)

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class E
Model Identifier 4053560234

