

Tubo Pro Pendant

67W / 5875lm / 3500K / DALI / Wide flood
76° / 2408mm

64930



Design: Eduardo Souto de Moura

Pendant luminaire with tubular semi frosted PMMA body with 70mm diameter.

Clear polycarbonate end caps with marked installation angles.

Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.

Equipped with 2m cable (5x0.75 mm²).

Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
Power supply included.
IP44 | 230Vac | 50/60Hz



| LED | 3500K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 67W | 78,1W |
| Flux | | 8640lm | 5875lm |
| Efficiency | | 130lm/W | 75lm/W |
| LOR | | - | 68% |
| UGR | | - | <19 |



Beam angle
Wide flood 76°

Application

Weight



Finishes

○ .01 White / RAL 9010

Mandatory

59147 Pendant fitting accessory (>2000mm)

Data according to regulations

2019/2020/EU supplemented by 2021/341 [2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class D
Model Identifier 4053560234

