

## One

9,8W / 770lm / 3000K / On/Off / Medium 40° / ø85mm

60149



Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Lightcore optics for defined and perfectly controlled beam of light.

Easy recessing system with spring clips.

Fitting accessories for different applications are available.

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



	105°
	90°
	75°
	60°
	450

Beam angle Medium 40°

## Application



Weight 0,53Kg



3000K

Power

Flux Efficiency

LOR

UGR

@078 (trim version)

Luminaire


12,3W

770lm

63lm/W

74%

<10



Light Source

9,8W

1035lm

106lm/W

## Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

## Optional

59014 Accessory 12,5mm ceilings (flush installation) 150x91x20mm

59038 Accessory 10-40mm ceilings (acoustic ceiling) 156×100×78mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class  $\ensuremath{\mathsf{F}}$ Model Identifier 2053560257H