

4,5W / 300lm / 3000K / DALI / Spot 15° /  
ø85mm

60154



Design: O/M + Bartenbach GmbH  
 Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.  
 Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam.  
 Fitting accessories for different applications are available.


LED CRI>90 / >50.000h, L80/B10  
 2-step MacAdam / Power supply included.  
 IP20 | 230Vac | 50/60Hz



LED 3000K

Light Source Luminaire

Power	4,5W	5,8W
Flux	520lm	300lm
Efficiency	116lm/W	52lm/W
LOR	-	58%
UGR	-	<10

Beam angle  
Spot 15°Weight  
0,58Kg

mm

Ø 078 (trim version)

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Optional

59014 Accessory 12,5mm ceilings (flush installation)

150x91x20mm

59038 Accessory 10-40mm ceilings (acoustic ceiling)

156x100x78mm

For the specific supply of "DALI 2" drivers, please contact:  
[support@om-light.com](mailto:support@om-light.com)

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains a light source of efficiency class F

Model Identifier 2053560257L

