

9,8W / 790lm / 4000K / On/Off / Spot 15° /
ø85mm

60163




Design: O/M + Bartenbach GmbH
 Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.
 Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam.
 Fitting accessories for different applications are available.

LED CRI>80 / >50.000h, L80/B10
 2-step MacAdam / Power supply included.
 IP20 | 230Vac | 50/60Hz



	4000K	Light Source	Luminaire
Power	9,8W	12,3W	
Flux	1360lm	790lm	
Efficiency	139lm/W	64lm/W	
LOR	-	58%	
UGR	-	<10	



Beam angle
Spot 15°



Application
Weight 0,58Kg

mm

Ø 078 (trim version)

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Optional


59014 Accessory 12,5mm ceilings (flush installation)

150x91x20mm

59038 Accessory 10-40mm ceilings (acoustic ceiling)

156x100x78mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com



Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains a light source of efficiency class F

Model Identifier 2053560247H