


One

9,8W / 1220lm / 4000K / On/Off / Flood 56° / ø85mm

60167



Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Lightcore optics for defined and perfectly controlled beam of light.

Easy recessing system with spring clips.

Fitting accessories for different applications are available.


LED CRI>80 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz





4000K	Light Source	Luminaire	
Power	9,8W	12,3W	
Flux	1360lm	1220lm	
Efficiency	139lm/W	100lm/W	
LOR	-	90%	
UGR	-	<19	

@078 (trim version)




Beam angle Flood 56°

Application



Weight 0,53Kg

mm			



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

Optional

59014 Accessory 12,5mm ceilings (flush installation)

150x91x20mm

59038 Accessory 10-40mm ceilings (acoustic ceiling) 156×100×78mm

The cutout dimensions are for plasterboard ceilings. For other type of $% \left\{ 1,2,\ldots ,n\right\}$ material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier 2053560247H