

One

4,5W / 360lm / 4000K / DALI / Spot 15° / ø85mm

60170



Design: O/M + Bartenbach GmbH Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester

paint finish.


Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam. Fitting accessories for different applications are available.

LED CRI>80 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz





1000K	Light Source	Luminaire
Power	4,5W	5,8W
Flux	620lm	360lm
Efficiency	138lm/W	62lm/W
LOR	-	58%
UGR	-	<10




Weight 0,58Kg

Beam angle Spot 15°

Application



@078 (trim version)



Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

Optional

59014 Accessory 12,5mm ceilings (flush installation) 150x91x20mm

59038 Accessory 10-40mm ceilings (acoustic ceiling) 156×100×78mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E Model Identifier 2053560247L