

4,5W / 470lm / 3000K / On/Off / Flood 56° /  
ø95mm

60235



Design: O/M + Bartenbach GmbH  
 Ceiling-recessed luminaire with die-cast aluminium body and heat sink.  
 Orientable by 30° on the horizontal axis and 355° on the vertical axis.  
 Reflector built based on micro surfaces with complex geometry coated with aluminium alloy, creating a high-gloss, entirely mirrored surface. Accurate reflector for a defined and controlled beam of light, achieving the maximum efficiency.  
 Reduced height <67mm.  
 Recessing accessory for trimless version supplied separately.

LED CRI>90 / >50.000h, L80/B10  
 2-step MacAdam / Power supply included.  
 IP20 | 230Vac | 50/60Hz



LED 3000K

Light Source

Luminaire

Power

4,5W

5,8W

Flux

520lm

470lm

Efficiency

116lm/W

81lm/W

LOR


-

90%

UGR

-

&lt;16



Beam angle  
Flood 56°

Application




Weight  
0,42Kg

mm

Ø90 (trim version)

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .21 Black+White



Optional

59015 Accessory 12,5mm ceilings (flush installation)  
 150x101x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains a light source of efficiency class F  
 Model Identifier 2053560257L