

4,5W / 470lm / 3000K / DALI / Flood 56° /
ø95mm

60237



Design: O/M + Bartenbach GmbH
 Ceiling-recessed luminaire with die-cast aluminium body and heat sink.
 Orientable by 30° on the horizontal axis and 355° on the vertical axis.
 Reflector built based on micro surfaces with complex geometry coated with aluminium alloy, creating a high-gloss, entirely mirrored surface. Accurate reflector for a defined and controlled beam of light, achieving the maximum efficiency.
 Reduced height <67mm.
 Recessing accessory for trimless version supplied separately.

LED CRI>90 / >50.000h, L80/B10
 2-step MacAdam / Power supply included.
 IP20 | 230Vac | 50/60Hz



LED 3000K

Light Source Luminaire


Power 4,5W 5,8W

Flux 520lm 470lm

Efficiency 116lm/W 81lm/W

LOR - 90%

UGR - <16



Beam angle
Flood 56°




Weight
0,42Kg

mm

∅ 90 (trim version)

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .21 Black+White



Optional
59015 Accessory 12,5mm ceilings (flush installation)
 150x101x20mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
 2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains a light source of efficiency class F
 Model Identifier 2053560257L