

4,5W / 560lm / 4000K / On/Off / Flood 56° /
ø95mm

60239




Design: O/M + Bartenbach GmbH
 Ceiling-recessed luminaire with die-cast aluminium body and heat sink.
 Orientable by 30° on the horizontal axis and 355° on the vertical axis.
 Reflector built based on micro surfaces with complex geometry coated with aluminium alloy, creating a high-gloss, entirely mirrored surface. Accurate reflector for a defined and controlled beam of light, achieving the maximum efficiency.
 Reduced height <67mm.
 Recessing accessory for trimless version supplied separately.

LED CRI>80 / >50.000h, L80/B10
 2-step MacAdam / Power supply included.
 IP20 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power	4,5W	5,8W	
Flux	620lm	560lm	
Efficiency	138lm/W	97lm/W	
LOR	-	90%	
UGR	-	<16	



Beam angle
Flood 56°



Weight
0,42Kg

mm

Ø90 (trim version)

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .21 Black+White

Optional

59015 Accessory 12,5mm ceilings (flush installation)
 150x101x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains a light source of efficiency class E
 Model Identifier 2053560247L

