

## Over Surface

9,8W / 930lm / 3000K / DALI / Flood 59° / ø85mm

60259



Design: O/M + Bartenbach GmbH Surface spotlight with die-cast aluminium body with electrostatic 100% polyester paint finish. Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam. Orientable by 90° horizontal rotation and 330° vertical rotation.


Driver included.

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



| C | E |
|---|---|
|   |   |


| ■ 3000K             | Light Source | Luminaire |  |
|---------------------|--------------|-----------|--|
| Power               | 9,8W         | 12,3W     |  |
| Flux                | 1035lm       | 930lm     |  |
| Efficiency          | 106lm/W      | 76lm/W    |  |
| LOR                 | -            | 90%       |  |
| Operating Condition | -            | 230Vac    |  |




Flood 59° Application Weight 0,64Kg

Beam angle

mm





## Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

## Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier 2053560257H